

PRODUCT DESCRIPTION

BEX® Premium Performance CI-4 PLUS Heavy Duty Diesel Engine Oils are specially formulated to provide extra protection in older diesel engines. Formulated for thermal endurance and viscosity stability. Utilizing pure virgin US base oils plus advanced additive technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle or equipment manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Superior cleaning power for extended engine performance
- Advanced protection against sludge, soot & varnish build up
- Superior additive technology retains viscosity & reduces engine wear
- Helps increase horsepower and fuel economy

TYPICAL PROPERTIES

TEST NAME	ASTM Method	10W-30	10W-40	15W-40	15W-50	20W-50
Kinematic Viscosity @ 100° C, cSt	D445	11.0	14.5	14.5	17.3	18.0
Kinematic Viscosity @ 40° C, cSt	D445	71.55	94.4	103.4	119.4	154.45
Viscosity Index	D2270	145	160	145	160	130
Flash Point °C / °F	D92	215 / 419	215 / 419	220 / 428	220 / 428	230 / 446
Pour Point °C / °F	D97	-38 / -36	-38 / -36	-34 / -29	-33 / -27	-30 / -22
TBN mgKOH/g	D2896	10	10	10	10	10
NOACK Volatility, %	D5800	11	11	10	10	8
Color	D1500	3	3	3	3	3

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B126Q	B127Q	B125Q	B129Q	B128Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B126L	B127L	B125L	B129L	B128L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B126G	B127G	B125G	B129G	B128G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B126P	B127P	B125P	B129P	B128P
Pail 20L	40.2	1.24	42	1735	B126J	B127J	B125J	B129J	B128J
Drum 208L (55 gl)	428	10.52	4	1760	B126D	B127D	B125D	B129D	B128D
Tote 1000L (265 gl)	1930	49.4	1	1930	B126T	B127T	B125T	B129T	B128T

TYPICAL APPLICATIONS

- Meets the performance requirement of API CI-4 Plus, CI-4, CH-4, CG-4, CF, SL, SJ and ACEA E2/E3, CAT ECF-1-a MTU-1, MB 228.1/229.1, Mack EO-M Plus, Cummins CES 20076, DDA 93K214, MAN 271, VW 501/505, MTU-1, Volvo VDS-2, Renault Truck RD/RD-2, JASO DH-1, Global DHD-1, ZF TE-ML 07C.

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

