

PRODUCT DESCRIPTION

BEX® Ultimate Performance Synthetic CK-4 Diesel Engine Oils are specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced synthetic technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- 100% synthetic technology to extend drain intervals
- Ultimate protection against sludge & soot for peak engine performance
- Synthetic additive technology retains viscosity & reduces engine wear
- Helps increase horsepower and fuel economy

TYPICAL PROPERTIES

TEST NAME	ASTM Method	5W-30	5W-40	10W-40	15W-40
Kinematic Viscosity @ 100° C, cSt	D445	10.8	14.5	14.5	14.5
Kinematic Viscosity @ 40° C, cSt	D445	66.1	91.75	94.4	100.25
Viscosity Index	D2270	155	165	160	150
Flash Point °C / °F	D92	210 / 410	215 / 419	215 / 419	225 / 437
Pour Point °C / °F	D97	-40 / -40	-40 / -40	-38 / -36	-35 / -31
TBN mgKOH/g	D2896	9	9	9	9
NOACK Volatility, %	D5800	12	11	10	9
Color	D1500	3.5	3.5	3.5	3.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B134Q	B135Q	B136Q	B137Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B134L	B135L	B136L	B137L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B134G	B135G	B136G	B137G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B134P	B135P	B136P	B137P
Pail 20L	40.2	1.24	42	1735	B134J	B135J	B136J	B137J
Drum 208L (55 gal)	428	10.52	4	1760	B134D	B135D	B136D	B137D
Tote 1000L (265 gal)	1930	49.4	1	1930	B134T	B135T	B136T	B137T

TYPICAL APPLICATIONS

- 5W-30 meets the performance requirement of API CK-4, ACEA E9, MB 228.51, Caterpillar ECF-3, Mack EOS 4.5, Cummins CES 20086, Detroit Diesel DFS 93K222, Renault VI RLD-4
- 5W-40 meets the performance requirements of API CK-4, ACEA E9, Allison C-4, MAN 3275/3575, DD DFS 93K222, MB 228.3/.31, Mack EO-0/EOS-4.5, MTU 2.1, Global DHD-1, Ford WSS-M2C171-E, Renault RLD-4, Volvo VDS-4

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.