

PRODUCT DESCRIPTION

BEX® Ultimate Performance European Formula Synthetic Oils are specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced synthetic technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Specially formulated for use in both gasoline & diesel fueled engines, plus turbo charged engines
- Ultimate protection against soot, sludge & wear for peak engine performance
- Lower ash content for compatibility in engines with diesel particulate filters (DPF)
- Helps maximize fuel economy & reduce emissions

TYPICAL PROPERTIES

TEST NAME	ASTM Method	0W-30 C2	5W-30 C3	5W-40 C3	0W-40 C3
Kinematic Viscosity @ 100° C, cSt	D445	9.8	11.0	14.5	13.5
Kinematic Viscosity @ 40° C, cSt	D445	50.5	62.65	86.8	77.2
Viscosity Index	D2270	185	170	175	180
Flash Point °C / °F	D92	205 / 401	210 / 410	210 / 410	205 / 401
Pour Point °C / °F	D97	-50 / -58	-44 / -47	-42 / -43	-48 / -44
Sulfated Ash, Wt %	D874	< 0.8	< 0.8	< 0.8	< 0.8
TBN, mgKOH/g	D2896	7.5	7.5	7.5	7.5
Color	D1500	2.5	2.5	2.5	2.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B133Q	B105Q	B107Q	B131Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B133L	B105L	B107L	B131L
Case 4/ 5L, net 20L	42.5	1.22	60	2170	B133G	B105G	B107G	B131G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B133P	B105P	B107P	B131P
Pail 20L	40.2	1.24	42	1735	B133J	B105J	B107J	B131J
Drum 208L (55 gal)	428	10.52	4	1760	B133D	B105D	B107D	B131D
Tote 1000L (265 gal)	1930	49.4	1	1930	B133T	B105T	B107T	B131T

TYPICAL APPLICATIONS

- 5W-30 meets the rigorous performance requirements of ACEA C3-16, A3/B4-08, API SN, BMW LL-01/LL-04, Daimler V2012.2, MB 229.31/229.51/229.53, Porsche C-30, Opel LL-A-025-B, VW 502 00/505 00/505 01
- 5W-40 and 0W-40 meet the performance requirements of ACEA C3-16, A3/B4-08, API:SN, BMW LL-01/LL-04, Porsche A-40, MB 229.31/229.51, Opel GM-LL-B-025, Renault 0710/0700, VW 501 01/502 00/505 00
- 0W-30 meets the performance requirements of ACEA C2-16

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.