

## PRODUCT DESCRIPTION

BEX® Gasoline Engine Oils Conventional SL are specially formulated to provide superior protection and effectively keep critical engine parts clean. Utilizing the best virgin base oil and premium additive technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

## FEATURES & BENEFITS

- Helps keep engines clean for peak engine performance
- Superior protection against sludge & soot build up
- Friction modifiers reduce engine wear
- Enhances fuel economy

## TYPICAL PROPERTIES

TEST NAME	ASTM Method	10W-40	15W-40	20W-50
Kinematic Viscosity @ 100° C, cSt	D445	14.5	14.5	18.0
Kinematic Viscosity @ 40° C, cSt	D445	91.75	103.4	154.45
Viscosity Index	D2270	165	145	130
Flash Point °C / °F	D92	210 / 410	220 / 428	230 / 446
Pour Point °C / °F	D97	-40 / -40	-35 / -31	-30 / -22
Specific Gravity @ 60°F	D4052	0.86	0.87	0.87
Appearance	D1500	Amber	Amber	Amber
Color	D1500	2.5	2.5	2.5

*Typical test data may vary. Minor variations, which do not affect performance, may occur.*

## PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B925Q	B926Q	B927Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B925L	B926L	B927L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B925G	B926G	B927G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B925P	B926P	B927P
Pail 20L	40.2	1.24	42	1735	B925J	B926J	B927J
Drum 208L (55 gl)	428	10.52	4	1760	B925D	B926D	B927D
Tote 1000L (265 gl)	1930	49.4	1	1930	B925T	B926T	B927T

## TYPICAL APPLICATIONS

- SAE 10W-40, 15W-40 and 20W-50 meet the performance requirements of API SL, SJ, CF
- 20W-50 has a higher viscosity reserve to fully protect engines under higher operating speeds, temperatures, and other adverse conditions

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

