



## ROCK DRILL OIL

### PRODUCT DESCRIPTION

BEX® Rock Drill Oils ISO 100, 150, 220, 320, 460 are blended from highly-refined, high viscosity-index base stocks and premium performance additives to provide maximum protection during the lubrication of pneumatic percussion tools including rock drills, jack hammers, pile drivers, chippers, pavement breakers and riveters. They are reinforced by extreme pressure performance additives specially designed to impart enhanced film strength, providing advanced protection and lubricity in extreme pressure conditions.

Premium performance additives provide excellent protection from rust and corrosion while maintaining excellent demulsibility to resist water washout. Plus, BEX® Rock Drill Oils demonstrate strong adherence to tool surfaces, critical for proper lubrication of pneumatic percussion tools. They are available in several viscosities dependent on the specific application.

### TYPICAL PROPERTIES\*

<u>TYPE</u>	<u>ISO 100</u>	<u>ISO 150</u>	<u>ISO 220</u>	<u>ISO 320</u>	<u>ISO 460</u>
Viscosity cSt @ 40°C	101.5	148.8	222.6	318.7	456.5
Viscosity cSt @ 100°C	12.1	16.29	22.03	26.33	34.99
Pour Point, °C	-24	-22	-23	-18	-20
Flash Point, °C	208	210	208	215	212
Viscosity Index	110	115	119	108	114
Appearance	Amber, Free & Clear				
Odor	Typical Lube Oil with Slight Sulfur Odor				

---

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

### SUITABLE FOR USE:

Rock drills, jack hammers, pile drivers, chippers, pavement breakers, riveters, and associated equipment.

Available in 5 gallon (18L) pails & 55 gallon (208L) drums