

PRODUCT DESCRIPTION

BEX® 4T Motorcycle Oils are specially formulated with EX³ to provide extra engine protection in three key areas: thermal stability, optimal friction characteristics and clutch protection. Utilizing advanced additive technology, BEX® oils meet or exceed current industry performance requirements. Always consult the equipment owner manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Delivers thermal stability in high RPM & temperature conditions
- Advanced anti-friction performance for power and smooth shifting
- Provides critical protection of the wet clutch

TYPICAL PROPERTIES

TEST NAME	ASTM Method	Syn Blend 10W-30	Syn Blend 10W-40	Mineral 20W-50
Kinematic Viscosity @ 100° C, cSt	D445	11.0	14.5	18.3
Kinematic Viscosity @ 40° C, cSt	D445	59.55	91.75	158.1
Viscosity Index	D2270	150	165	130
Flash Point °C / °F	D92	215 / 419	210 / 410	220 / 428
Pour Point °C / °F	D97	-40 / -40	-40 / -40	-30 / -22
Specific Gravity @ 60°F	D4052	0.87	0.86	0.87
NOACK Volatility, %	D5800	11	13	8
Color	D1500	2.5	2.5	2.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B206Q	B207Q	B208Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B206L	B207L	B208L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B206G	B207G	B208G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B206P	B207P	B208P
Pail 20L	40.2	1.24	42	1735	B206J	B207J	B208J
Drum 208L (55 gal)	428	10.52	4	1760	B206D	B207D	B208D
Tote 1000L (265 gal)	1930	49.4	1	1930	B206T	B207T	B208T

TYPICAL APPLICATIONS

- SAE 10W-30, 10W-40 and 20W-50 meet the requirements of JASO MA, MA-2 and API SL
- 20W-50 has a higher viscosity reserve to fully protect four stroke engines under higher operating speeds, temperatures, and other adverse conditions
- Recommend for use in motorcycles, scooters, ATVs and other small four stroke recreational engines

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.